

機器名 (備考)	バス幅 (bit)	KByte/s	MByte/s	bps	Kbps	Mbps	10BASEを1とした時
i-mode (データ通信)		1.2	0.00	9,600	9.6	0.01	0.0
ezweb (データ通信)		1.8	0.00	14,000	14.0	0.01	0.0
28.8k モデム		3.6	0.00	28,800	28.8	0.03	0.0
33.6k モデム		4.2	0.00	33,600	33.6	0.03	0.0
56k モデム		7.0	0.01	56,000	56.0	0.06	0.0
ISDN		8.0	0.01	64,000	64.0	0.06	0.0
ISDN (2)		16.0	0.02	128,000	128.0	0.13	0.0
ケーブルモデム (CATV会社により異なる)		64.0	0.06	512,000	512.0	0.51	0.1
ADSL (料金体系により上限変化)		187.5	0.19	1,500,000	1500.0	1.50	0.2
PIAFS (PHS32k)		4.0	0.00	32,000	32.0	0.03	0.0
PIAFS (PHS64k)		8.0	0.01	64,000	64.0	0.06	0.0
PacketOne64 (cdmaOne)		8.0	0.01	64,000	64.0	0.06	0.0
専用線接続 (OCNスタンダード等)		187.5	0.19	1,500,000	1500.0	1.50	0.2
専用線接続 (OCNエンタープライズ等)		750.0	0.75	6,000,000	6000.0	6.00	0.6

専用線接続 (IIJ 等)		5625.0	5.63	45,000,000	45000.0	45.00	4.5
専用線接続 (IIJ 等)		19375.0	19.38	155,000,000	155000.0	155.00	15.5
専用線接続 (WIDE 等)		25000.0	25.00	200,000,000	200000.0	200.00	20.0
無線 LAN (IEEE802.11)		250.0	0.25	2,000,000	2000.0	2.00	0.2
無線 LAN (IEEE802.11 b)		1375.0	1.38	11,000,000	11000.0	11.00	1.1
Bluetooth (IEEE802.15)		250.0	0.25	2,000,000	2000.0	2.00	0.2
10BASE-T Ethernet (IEEE802.3)		1250.0	1.25	10,000,000	10000.0	10.00	1.0
100 BASE-TX Ethernet (IEEE802.3 u)		12500.0	12.50	100,000,000	100000.0	100.00	10.0
1000 BASE-SX Ethernet (IEEE802.3 z)		125000.0	125.00	1,000,000,000	1000000.0	1000.00	100.0
FDDI (ANSI FDDI X3 T9.5 SMT)		12500.0	12.50	100,000,000	100000.0	100.00	10.0
ATM (ATM Forum UNI3.0, 3.1)		62500.0	62.50	500,000,000	500000.0	500.00	50.0
RS-232C (8250 等)		1.2	0.00	9,600	9.6	0.01	0.0
RS-232C (16550 等)		14.4	0.01	115,200	115.2	0.12	0.0
セントロニクス		250.0	0.25	2,000,000	2000.0	2.00	0.2

双方向パラレル (IEEE1284)		2000.0	2.00	16,000,000	16000.0	16.00	1.6
MIDI		3.9	0.00	31,250	31.3	0.03	0.0
mLAN (IEEE1394 互換)		50000.0	50.00	400,000,000	400000.0	400.00	40.0
GP-IB (IEEE488) (最大)		1000.0	1.00	8,000,000	8000.0	8.00	0.8
HS GP-IB (最大)		8000.0	8.00	64,000,000	64000.0	64.00	6.4
IrDA1.0 (赤外線通信)		1.4	0.00	11,520	11.5	0.01	0.0
IrDA1.1 (赤外線通信)		4000.0	4.00	32,000,000	32000.0	32.00	3.2
USB1.1 (Low スピードモード)		187.5	0.19	1,500,000	1500.0	1.50	0.2
USB1.1 (Full スピードモード)		1500.0	1.50	12,000,000	12000.0	12.00	1.2
USB2.0 (最大)		60000.0	60.00	480,000,000	480000.0	480.00	48.0
FireWire (IEEE1394) (低)		12500.0	12.50	100,000,000	100000.0	100.00	10.0
FireWire (IEEE1394) (中)		25000.0	25.00	200,000,000	200000.0	200.00	20.0
FireWire (IEEE1394) (高)		50000.0	50.00	400,000,000	400000.0	400.00	40.0
FireWire2? (IEEE1394b) (低)		100000.0	100.00	800,000,000	800000.0	800.00	80.0

FireWire2? (IEEE1394b) (高)		200000.0	200.00	1,600,000,000	1600000.0	1600.00	160.0
FireWire2? (IEEE1394b) (光)		400000.0	400.00	3,200,000,000	3200000.0	3200.00	320.0
CAMAC (IEEE 538)	24	1000.0	1.00	8,000,000	8000.0	8.00	0.8
VME (IEEE 1014)	32	20000.0	20.00	160,000,000	160000.0	160.00	16.0
VXI (IEEE 1155)	32	40000.0	40.00	320,000,000	320000.0	320.00	32.0
PXI	32/64	132000.0	132.00	1,056,000,000	1056000.0	1056.00	105.6
C-Bus (NEC PC-9801)	16	10000.0	10.00	80,000,000	80000.0	80.00	8.0
NuBUS (Apple 旧 Macintosh)	32	37500.0	37.50	300,000,000	300000.0	300.00	30.0
ISA	8/16	8330.0	8.33	66,640,000	66640.0	66.64	6.7
EISA	8/16/32	33000.0	33.00	264,000,000	264000.0	264.00	26.4
PCI	32/64	132000.0	132.00	1,056,000,000	1056000.0	1056.00	105.6
AGP (bus clock 66 MHz)	32	266000.0	266.00	2,128,000,000	2128000.0	2128.00	212.8
AGP (bus clock 133 MHz)	32	533000.0	533.00	4,264,000,000	4264000.0	4264.00	426.4
PCMCIA	16	16000.0	16.00	128,000,000	128000.0	128.00	12.8
Card Bus	16/32	132000.0	132.00	1,056,000,000	1056000.0	1056.00	105.6
ATA (IDE)	16/32	8330.0	8.33	66,640,000	66640.0	66.64	6.7
FAST ATA (E-IDE)	32	16660.0	16.66	133,280,000	133280.0	133.28	13.3
Ultra ATA-33 (ATA/ATAPI-4)	32	33330.0	33.33	266,640,000	266640.0	266.64	26.7

Ultra ATA-66 (Fast ATA-2)	32	66660.0	66.66	533,280,000	533280.0	533.28	53.3
Ultra ATA/100 (Ultra DMA/100)	32	100000.0	100.00	800,000,000	800000.0	800.00	80.0
SCSI	8	5000.0	5.00	40,000,000	40000.0	40.00	4.0
Fast SCSI	8	10000.0	10.00	80,000,000	80000.0	80.00	8.0
Ultra SCSI	8	20000.0	20.00	160,000,000	160000.0	160.00	16.0
Wide SCSI	16/32	20000.0	20.00	160,000,000	160000.0	160.00	16.0
Ultra Wide SCSI	16	40000.0	40.00	320,000,000	320000.0	320.00	32.0
Ultra2 SCSI	32	80000.0	80.00	640,000,000	640000.0	640.00	64.0
Ultra160 SCSI	32/64	160000.0	160.00	1,280,000,000	1280000.0	1280.00	128.0