

<http://oku.edu.mie-u.ac.jp/~okumura/java2/test.html>

方法 1

```
<applet code="Lesson4.class" width="300" height="100">  
No Way  
</applet>  
No Way
```

MSIE 6 / Firefox 1.5 / Firefox 2 / Safari 2 / MSIE 5.2.3 for Mac

方法 2

```
<object codetype="application/java"  
classid="java:Lesson4.class"  
width="300" height="100">  
No Way  
</object>  
No Way
```

Firefox 1.5 / Firefox 2 / MSIE 5.2.3 for Mac

方法 3

```
<object codetype="application/java"  
type="application/x-java-applet"  
classid="java:Lesson4.class"  
width="300" height="100">  
No Way  
</object>  
No Way
```

Firefox 1.5 / Firefox 2 / Safari 2 / MSIE 5.2.3 for Mac

方法 4

```
<object classid="clsid:8AD9C840-044E-11D1-B3E9-00805F499D93"  
type="application/x-java-applet"  
codetype="application/java"  
width="300" height="100">  
<param name="code" value="Lesson4.class">  
No Way  
</object>  
No Way
```

MSIE 6 / Safari 2 / MSIE 5.2.3 for Mac

方法 5

```
<!--[if !IE]>-->  
<object classid="java:Lesson4.class"  
type="application/x-java-applet"  
width="300" height="100">  
<!--<![endif]>-->  
<object classid="clsid:8AD9C840-044E-11D1-B3E9-00805F499D93"  
width="300" height="100">  
<param name="code" value="Lesson4" />  
No Way  
</object>  
<!--[if !IE]>-->
```

```
</object>  
<!--<![endif]-->  
No Way
```

MSIE 6 / Firefox 1.5 / Firefox 2 / Safari 2 / MSIE 5.2.3 for Mac (with an extra "No Way")

Note: The conditional Comments only apply to Windows IE 5.0 and newer.